


JE-LiHCH



Primena: Za prenos signala između elektronskih uređaja, u računarskim sistemima ili jedinicama za kontrolu procesa sa povećanim zahtevima na elektromagnetnu kompatibilnost.

Application: For signal transmission between electronic devices, in computer systems or process control units with increased requirements to electromagnetic compatibility.

Materijal provodnika:	bakar
Konstrukcija provodnika:	klasa 5
Izolacija:	bezhalogeno jedinjenje HI1
Ekran:	Cu-pletunica
Materijal plašta:	bezhalogeno jedinjenje HM2
Otpornost na plamen:	VDE 0482-266-2-4/IEC 60332-3-24 (Kat. C)
Gustina dima:	DIN EN 61034/IEC 61034
Bez halogena:	DIN EN 50267/IEC 60754
Maksimalna temperatura tokom rada:	-30 - +70 °C
Dozvoljena temperatura tokom poleganja:	-5 - +70 °C
Radni kapacitet:	120 nF/km
Nominalni naponski nivo U₀:	250 V
Ispitni naponski nivo:	1,2 kV
Obeležavanje žila:	boje + prstenovi

Conductor material:	bare copper
Conductor construction:	fine stranded, class 5
Insulation:	FRNC compound HI1
Screen:	Cu-braiding
Sheathing material:	FRNC-compound HM2
Flame retardant:	VDE 0482-266-2-4/IEC 60332-3-24 (Kat. C)
Smoke density:	DIN EN 61034/IEC 61034
Halogen free:	DIN EN 50267/IEC 60754
Max. operating temperature, fixed:	-30 - +70 °C
Temperature, moved/ during installation:	-5 - +70 °C
Bending radius, fixed installation:	7,5 x DA
Insulation resistance:	20 MOhm \times km
Specific inductivity:	0,65 mH/km
Operating capacity:	120 nF/km
Nominal voltage U₀:	250 V
Test voltage:	1,2 kV
Core identification:	colours + rings

JE-LiHCH

Naziv kabla	Presek	Boja	Da	T	CU
Cable name	Cross section	Color	mm	kg/km	kg/km
JE-LiHCH	02X2X0,5 Bd Si	siva / gray	9,1	92	48
JE-LiHCH	04X2X0,5 Bd Si	siva / gray	10,3	155	84
JE-LiHCH	08X2X0,5 Bd Si	siva / gray	13,3	250	152
JE-LiHCH	12X2X0,5 Bd Si	siva / gray	15,6	315	193
JE-LiHCH	16X2X0,5 Bd Si	siva / gray	17,1	389	243

Naziv kabla	Presek	Boja	Da	T	CU
Cable name	Cross section	Color	mm	kg/km	kg/km
JE-LiHCH	20X2X0,5 Bd Si	siva / gray	18,5	457	292
JE-LiHCH	24X2X0,5 Bd Si	siva / gray	20,8	556	342
JE-LiHCH	32X2X0,5 Bd Si	siva / gray	23,5	680	435
JE-LiHCH	40X2X0,5 Bd Si	siva / gray	25,2	823	531
JE-LiHCH	48X2X0,5 Bd Si	siva / gray	25,9	988	665

Objašnjenje oznaka

Da Spoljni dijametar
T Ukupna težina kabla
Cu Težina bakra u kablu

Labels explanation

Da Outer diameter
T Total weight
Cu Copper weight

