


Optical Dataline I-V(ZN)H



Primena: Zatvoreni distributivni kabl sa čvrstim ublaživačem i bezhalogenim omotačem. Za montažu na nosače kablova i u vodovima. Kabl nudi do 24 vlakna, koja se mogu direktno spojiti sa konektorima i pogodni su za montažu na terenu.

Application: Indoor distribution cable with tight buffers and LSOH jacket. For installation on cable trays and ducts. The cable offers up to 24 fibers, which may be directly assembled to connectors and are suitable for field-assembly.

Kvalitet vlakana:	vidi stranicu za vlakna
Element:	čvrst ublaživač
Bez metala:	da
Materijal plašta:	bezhalogeno jedinjenje HM1
Otpornost na plamen:	VDE 0482-332-1-2/IEC 60332-1
Maksimalna temperatura tokom rada:	-20 - 60 °C
Dozvoljena temperatura tokom poleganja:	-20 - 60 °C

Fiber quality:	see data-sheet for fibers
Element:	tight buffer
Metal free:	yes
Sheathing material:	FRNC-compound HM1
Flame retardant:	VDE 0482-332-1-2/IEC 60332-1
Max. operating temperature, fixed:	-20 - 60 °C
Temperature, moved /during installation:	-20 - 60 °C

Optical Dataline I-V(ZN)H

Naziv kabla	Presek	Boja	Da	SK	VK	MKO	ZČP	ES	T	RSZ	RSbZ	OG
Cabl name	Crosssection	Color	mm	mm	mm	N	N	kWh/m	kg/km	mm	mm	N
I-V(ZN)H	2X1G50/125 Standard	narandž. / orange	6	10	6	450	250	0,11	19,3	40	40	200
I-V(ZN)H	2X1G50/125 High Grade	narandž. / orange	6	10	6	450	250	0,11	19	40	40	200
I-V(ZN)H	2X1G62,5/125 Standard	narandž. / orange	6	10	6	450	250	0,11	19,3	40	40	200
I-V(ZN)H	1X4G50/125 Standard	narandž. / orange	5,1			1500	1000	0,11	32	75	51	200
I-V(ZN)H	1X4G50/125 High Grade	narandž. / orange	5,1			1500	1000	0,11	32	75	51	200
I-V(ZN)H	1X4G62,5/125 Standard	narandž. / orange	5,1			1500	1000	0,11	32	75	51	200
I-V(ZN)H	1X6G50/125 Standard	narandž. / orange	5,5			1500	1000	0,14	36	85	57	200
I-V(ZN)H	1X6G62,5/125 Standard	narandž. / orange	5,5			1500	1000	0,14	36	85	57	200
I-V(ZN)H	1X8G50/125 Standard	narandž. / orange	5,7			1500	1000	0,14	36	85	57	200
I-V(ZN)H	1X8G62,5/125 Standard	narandž. / orange	5,7			1500	1000	0,14	36	85	57	200
I-V(ZN)H	1X10G50/125 Standard	narandž. / orange	6,5			1500	1000	0,18	41	100	65	200
I-V(ZN)H	1X10G62,5/125 Standard	narandž. / orange	6,5			1500	1000	0,18	41	100	65	200
I-V(ZN)H	1X12G50/125 Standard	narandž. / orange	6,5			1500	1000	0,18	41	100	65	200
I-V(ZN)H	1X12G62,5/125 Standard	narandž. / orange	6,5			1500	1000	0,18	41	100	65	200

Objašnjenje oznaka

Da	Spoljni dijametar
SK	Širina kabla
VK	Visina kabla
MKO	Momenat kidanja prilikom poleganja
ZČP	Zatezna čvrstoća(permanentno)
ES	Energija sagorevanja
T	Ukupna težina kabla
RSZ	Radijus savijanja sa opterećenjem zatezanja
RSbZ	Radijus savijanja bez opterećenja zatezanja
OG	Otpor gnječenja

Labels explanation

Da	Outer diameter
SK	Cable width
VK	Cable high
MKO	Tensile strength (during installation)
ZČP	Tensile strength (permanent)
ES	Combustion energy
T	Total weight
RSZ	Bending radius with tension load
RSbZ	Bending radius without tension load
OG	Crush resistance

